

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/07/2016

Reviewed on 09/07/2016

1 Identification

Product Identifier**Trade name: Precision Calibration Gas Mixture****Product Number:** G-2015**Relevant identified uses of the substance or mixture and uses advised against:**

Used for calibration of gas measuring devices. Not suitable for human consumption.

Product Description Calibration gas mixture consisting of Carbon Monoxide, Oxygen and Nitrogen.**Details of the Supplier of the Safety Data Sheet:****Manufacturer/Supplier:**

Gasco Affiliates, LLC

320 Scarlett Blvd.

Oldsmar, FL 34677

TELEPHONE NUMBER: (800) 910-0051

FAX NUMBER: (866) 755-8920

E-MAIL: info@gascogas.com

Emergency telephone number:

Inside the US: 1-800-424-9300 (CHEMTREC, 24 hours)

Outside the US: 1-703-527-3887 (CHEMTREC, 24 hours)

2 Hazard(s) Identification

Classification of the substance or mixture:

GHS03 Flame over circle

Oxid. Gas 1 H270 May cause or intensify fire; oxidizer.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Repr. 1 H360 May damage fertility or the unborn child.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

Simple Asphyxiant May displace oxygen and cause rapid suffocation.

Label elements:**GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/07/2016

Reviewed on 09/07/2016

Trade name: Precision Calibration Gas Mixture**Hazard pictograms:**

GHS03 GHS04 GHS06 GHS08

Signal word: Danger**Hazard-determining components of labeling:**

Nitrogen
Carbon Monoxide
Oxygen

Hazard statements:

H270 May cause or intensify fire; oxidizer.
H280 Contains gas under pressure; may explode if heated.
H331 Toxic if inhaled.
H360 May damage fertility or the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
May displace oxygen and cause rapid suffocation.

Precautionary statements:

P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P220 Keep/Store away from clothing/combustible materials.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P244 Keep valves and fittings free from oil and grease.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
P311 Call a POISON CENTER/doctor.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P314 Get medical advice/attention if you feel unwell.
P370+P376 In case of fire: Stop leak if safe to do so.
P405 Store locked up.
P410+P403 Protect from sunlight. Store in a well-ventilated place.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

100 % of the mixture consists of component(s) of unknown toxicity.

Classification system:**NFPA ratings (scale 0 - 4)**

Health = 2
Fire = 1
Reactivity = 0

The substance possesses oxidizing properties.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/07/2016

Reviewed on 09/07/2016

Trade name: Precision Calibration Gas Mixture**· HMIS-ratings (scale 0 - 4)**

| | | |
|------------|----|----------------|
| HEALTH | *2 | Health = *2 |
| FIRE | 1 | Fire = 1 |
| REACTIVITY | 0 | Reactivity = 0 |

· Hazard(s) not otherwise classified (HNOC): None known*** 3 Composition/Information on Ingredients****· Chemical characterization: Mixtures****· Description:** Mixture of substances listed below with non-hazardous additions.**· Dangerous Components:**

| | | |
|-------------------------------------|--|--------------|
| CAS: 7727-37-9 RTECS: QW 9700000 | Nitrogen ⚠ Press. Gas, H280; Simple Asphyxiant | 2 - 76.3499% |
| CAS: 7782-44-7 | Oxygen ⚠ Oxid. Gas 1, H270; ⚠ Press. Gas, H280 | 23.5 - 93% |
| CAS: 630-08-0 RTECS: FG 3500000 | Carbon Monoxide ⚠ Flam. Gas 1, H220; ⚠ Acute Tox. 3, H331; ⚠ Repr. 1A, H360; STOT RE 1, H372; Press. Gas, H280 | 0.00005 - 5% |

4 First-Aid Measures**· Description of first aid measures:****· After inhalation:**

Get medical attention immediately. Move person to fresh air. If it is expected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Generally the product does not irritate the skin.

In cases of contact with liquified material, frostbite may occur. Immerse frostbite in cool-warm water and seek medical attention.

· After eye contact:

Not anticipated under normal use.

If irritation occurs thoroughly wash the exposed area and discontinue use. Seek medical attention if any adverse effect occurs.

· After swallowing: If swallowed and symptoms occur, consult a doctor.**· Information for doctor:****· Most important symptoms and effects, both acute and delayed:** No further relevant information available.**· Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

5 Fire-Fighting Measures**· Extinguishing media:****· Suitable extinguishing agents:**

Use fire fighting measures that suit the environment.

Use water spray to cool fire-exposed containers.

· Special hazards arising from the substance or mixture:

Closed containers may explode when exposed to extreme heat.

If incinerated, product will release the following toxic fumes: Oxides of Carbon and Nitrogen (NOx).

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/07/2016

Reviewed on 09/07/2016

Trade name: Precision Calibration Gas Mixture

- **Advice for firefighters:**

Certain variations of this gas mixture may contain high concentrations of Oxygen which acts as an oxidizer and may intensify any fires.

- **Protective equipment:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Treat any fumes as toxic.

Keep people at a distance and stay upwind.

- **Environmental precautions:** Inform authorities in case of gas release.

- **Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

- **Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- **Handling**

- **Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Be aware of any signs of dizziness or fatigue; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms due to the potential for oxygen deficiency (simple asphyxiation). Do not attempt to adjust, repair or in any other way modify the cylinders containing this gas mixture. If there is a malfunction or another type of operational problem, contact nearest distributor immediately.

- **Information about protection against explosions and fires:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Keep protective respiratory device available.

Do not cut, grind or weld on container that contains or contained product.

Do not spray on a naked flame or any incandescent material.

- **Conditions for safe storage, including any incompatibilities:**

Store away from strong oxidizing agents, phosphorous, organic materials, Alkali metals, metal oxides and powdered metals.

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Cylinders should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature. Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a "first-on, first-out" inventory system to prevent full containers from being stored for long periods of time.

- **Information about storage in one common storage facility:** Not required.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/07/2016

Reviewed on 09/07/2016

Trade name: Precision Calibration Gas Mixture

- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s):** No further relevant information available.

8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**
All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.
- **Components with occupational exposure limits:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

| 7727-37-9 Nitrogen | |
|---------------------------------|--|
| TLV | withdrawn TLV, see App. F; simple asphyxiant |
| 630-08-0 Carbon Monoxide | |
| PEL | Long-term value: 55 mg/m ³ , 50 ppm |
| REL | Long-term value: 40 mg/m ³ , 35 ppm Ceiling limit value: 229 mg/m ³ , 200 ppm |
| TLV | Long-term value: 29 mg/m ³ , 25 ppm BEI |

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.
- **Exposure controls:**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
- **Breathing equipment:**



Suitable respiratory protective device recommended.

- **Protection of hands:** Not required.
- **Eye protection:** Not necessary under normal conditions.

9 Physical and Chemical Properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
 - **Form:** Gaseous
 - **Color:** Clear, colorless
 - **Odor:** Odorless
 - **Odor threshold:** Not determined.
 - **pH-value:** Not determined.
- **Change in condition**
 - **Melting point/Melting range:** Not determined.
 - **Boiling point/Boiling range:** -195 °C (-319 °F)

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/07/2016

Reviewed on 09/07/2016

Trade name: Precision Calibration Gas Mixture

- **Flash point:** None
- **Flammability (solid, gaseous):** Contact with combustible material may cause fire.
- **Ignition temperature:**
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Not determined.
- **Explosion limits:**
- **Lower:** Not determined.
- **Upper:** Not determined.
- **Vapor pressure:** Not determined.
- **Density @ 20 °C (68 °F):** 0.001 g/cm³ (0.008 lbs/gal)
- **Relative density:** Not determined.
- **Vapor density:** Not determined.
- **Evaporation rate:** Not applicable.
- **Solubility in / Miscibility with:**
- **Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
- **Dynamic:** Not determined.
- **Kinematic:** Not determined.
- **Solvent content:**
- **Organic solvents:** 0.0 %
- **Other information:** No further relevant information available.

10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:**
Strong oxidizing agents, phosphorous, organic materials, Alkali metals, metal oxides and powdered metals.
- **Hazardous decomposition products:** Carbon Oxides and Nitrogen Oxides (NOx).

11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

630-08-0 Carbon Monoxide

| | | |
|------------|----------|-----------------|
| Inhalative | LC50/4 h | 7520 mg/l (rat) |
|------------|----------|-----------------|

- **Primary irritant effect:**
- **On the skin:** No irritating effect.
- **On the eye:** No irritating effect.

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/07/2016

Reviewed on 09/07/2016

Trade name: Precision Calibration Gas Mixture**· Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories:**· IARC (International Agency for Research on Cancer):**

- Group 1 - Carcinogenic to humans
- Group 2A - Probably carcinogenic to humans
- Group 2B - Possibly carcinogenic to humans
- Group 3 - Not classifiable as to its carcinogenicity to humans
- Group 4 - Probably not carcinogenic to humans

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

12 Ecological Information

- **Toxicity:** The hazards for the aquatic environment are unknown.
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Generally not hazardous for water.
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

13 Disposal Considerations

- **Waste treatment methods:**
- **Recommendation:**
Release all residual gas pressure in a well ventilated area. Verify the cylinder is completely empty (0 PSIG). Remove or cover any hazard labels. Return empty cylinder for recycling.
NOTE: Check with the local waste authority before placing any gas cylinder into waste container for pickup. GASCO encourages the consumer to return all cylinders.
- **Waste disposal key:**
The U.S. EPA has not published waste disposal numbers for this product's components.
- **Uncleaned packagings**
- **Recommendation:** Return cylinder and unused product to supplier.

14 Transport Information

- **UN-Number:**
- **DOT, ADR, IMDG, IATA** UN3156
- **UN proper shipping name:**
- **DOT** Compressed gas, oxidizing, n.o.s.
- **ADR** UN3156 Compressed gas, oxidizing, n.o.s.
- **IMDG, IATA** COMPRESSED GAS, OXIDIZING, N.O.S.

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/07/2016

Reviewed on 09/07/2016

Trade name: Precision Calibration Gas Mixture· **Transport hazard class(es):**· **DOT**


· **Class:** 2 Gases
 · **Label:** 2.2, 5.1

· **ADR**

· **Class:** 2 10 Gases
 · **Label:** 2.2+5.1

· **IMDG**

· **Class:** 2 Gases
 · **Label:** 2.2/5.1

· **IATA**

· **Class:** 2 Gases
 · **Label:** 2.2 (5.1)
 · **Packing group:**
 · **DOT, ADR, IMDG, IATA** Non-Regulated Material
 · **Environmental hazards:** Not applicable.
 · **Special precautions for user:** Warning: Gases
 · **Danger code (Kemler):** 25
 · **EMS Number:** F-C,S-W
 · **Stowage Category** D
 · **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
 · **Transport/Additional information:**
 · **DOT**
 · **Quantity limitations:** On passenger aircraft/rail: 75 kg
 On cargo aircraft only: 150 kg

· **ADR**

· **Excepted quantities (EQ):** Code: E0
 Not permitted as Excepted Quantity

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/07/2016

Reviewed on 09/07/2016

Trade name: Precision Calibration Gas Mixture

- **IMDG**
- **Limited quantities (LQ):** 0
- **Excepted quantities (EQ):** Code: E0
Not permitted as Excepted Quantity
- **UN "Model Regulation":** UN 3156 COMPRESSED GAS, OXIDIZING, N.O.S., 2.2 (5.1)

15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

| |
|--|
| · Section 355 (extremely hazardous substances): |
|--|

| |
|-------------------------------------|
| None of the ingredients are listed. |
|-------------------------------------|

| |
|--|
| · Section 313 (Specific toxic chemical listings): |
|--|

| |
|-------------------------------------|
| None of the ingredients are listed. |
|-------------------------------------|

| |
|---|
| · TSCA (Toxic Substances Control Act): |
|---|

| |
|--|
| All ingredients are listed or exempt from listing. |
|--|

| |
|-------------------------------------|
| · California Proposition 65: |
|-------------------------------------|

| |
|---|
| · Chemicals known to cause cancer: |
|---|

| |
|-------------------------------------|
| None of the ingredients are listed. |
|-------------------------------------|

| |
|--|
| · Chemicals known to cause reproductive toxicity for females: |
|--|

| |
|-------------------------------------|
| None of the ingredients are listed. |
|-------------------------------------|

| |
|--|
| · Chemicals known to cause reproductive toxicity for males: |
|--|

| |
|-------------------------------------|
| None of the ingredients are listed. |
|-------------------------------------|

| |
|---|
| · Chemicals known to cause developmental toxicity: |
|---|

| |
|-------------------------------------|
| None of the ingredients are listed. |
|-------------------------------------|

| |
|-----------------------------------|
| · Carcinogenic categories: |
|-----------------------------------|

| |
|---|
| · EPA (Environmental Protection Agency): |
|---|

| |
|-------------------------------------|
| None of the ingredients are listed. |
|-------------------------------------|

| |
|--|
| · TLV (Threshold Limit Value established by ACGIH): |
|--|

| |
|-------------------------------------|
| None of the ingredients are listed. |
|-------------------------------------|

| |
|--|
| · NIOSH-Ca (National Institute for Occupational Safety and Health): |
|--|

| |
|-------------------------------------|
| None of the ingredients are listed. |
|-------------------------------------|

| |
|-----------------------------|
| · GHS label elements |
|-----------------------------|

| |
|--|
| The product is classified and labeled according to the Globally Harmonized System (GHS). |
|--|

| |
|-----------------------------|
| · Hazard pictograms: |
|-----------------------------|



GHS03 GHS04 GHS06 GHS08

| |
|------------------------------|
| · Signal word: Danger |
|------------------------------|

| |
|---|
| · Hazard-determining components of labeling: |
|---|

| |
|-----------------|
| Nitrogen |
| Carbon Monoxide |
| Oxygen |

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/07/2016

Reviewed on 09/07/2016

Trade name: Precision Calibration Gas Mixture**· Hazard statements:**

- H270 May cause or intensify fire; oxidizer.
- H280 Contains gas under pressure; may explode if heated.
- H331 Toxic if inhaled.
- H360 May damage fertility or the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- May displace oxygen and cause rapid suffocation.

· Precautionary statements:

- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P220 Keep/Store away from clothing/combustible materials.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P244 Keep valves and fittings free from oil and grease.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P311 Call a POISON CENTER/doctor.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P370+P376 In case of fire: Stop leak if safe to do so.
- P405 Store locked up.
- P410+P403 Protect from sunlight. Store in a well-ventilated place.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**16 Other Information****· Relevant phrases:**

Gasco Affiliates, LLC, makes not express or implied warranties, guarantees or representations regarding the product of the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Gasco Affiliates, LLC shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use of reliance upon the information herein.

· Date of preparation / last revision: 09/07/2016 / -**· Abbreviations and acronyms:**

- ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMSI: Hazardous Materials Identification System (USA)
- LC50: Lethal concentration, 50 percent

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/07/2016

Reviewed on 09/07/2016

Trade name: Precision Calibration Gas Mixture

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Gas 1: Flammable gases – Category 1
Oxid. Gas 1: Oxidizing gases – Category 1
Press. Gas: Gases under pressure – Compressed gas
Press. Gas: Gases under pressure – Dissolved gas
Acute Tox. 3: Acute toxicity – Category 3
Repr. 1: Reproductive toxicity – Category 1
Repr. 1A: Reproductive toxicity – Category 1A
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

*** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106