

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/09/2015

Reviewed on 11/09/2015

* 1 Identification

· **Product Identifier**

· **Trade name: Precision Calibration Gas Mixture**

· **Product Number:** G-15315

· **Relevant identified uses of the substance or mixture and uses advised against:**

Used for calibration of gas measuring devices. Not suitable for human consumption.

· **Product Description** Calibration gas mixture consisting of Hydrogen Sulfide, Sulfur Dioxide and Nitrogen.

· **Details of the Supplier of the Safety Data Sheet:**

· **Manufacturer/Supplier:**

Gasco Affiliates, LLC

320 Scarlett Blvd.

Oldsmar, FL 34677

TELEPHONE NUMBER: (800) 910-0051

FAX NUMBER: (866) 755-8920

E-MAIL: info@gascogas.com

· **Emergency telephone number:**

Inside the US: 1-800-424-9300 (CHEMTREC, 24 hours)

Outside the US: 1-703-527-3887 (CHEMTREC, 24 hours)

* 2 Hazard(s) Identification

· **Classification of the substance or mixture:**



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Simple Asphyxiant May displace oxygen and cause rapid suffocation.

· **Label elements:**

· **GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



GHS04 GHS07

· **Signal word:** Warning

· **Hazard statements:**

Contains gas under pressure; may explode if heated.

Harmful if inhaled.

May displace oxygen and cause rapid suffocation.

· **Precautionary statements:**

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/09/2015

Reviewed on 11/09/2015

Trade name: Precision Calibration Gas Mixture

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.
Protect from sunlight. Store in a well-ventilated place.

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMSI-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

- **Hazard(s) not otherwise classified (HNOC):** None known

* **3 Composition/Information on Ingredients**

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with non-hazardous additions.

· **Dangerous Components:**

CAS: 7783-06-4	Hydrogen Sulfide ⚠ Flam. Gas 1, H220; ⚠ Acute Tox. 2, H330; ⚠ Aquatic Acute 1, H400; Press. Gas, H280	0.001-0.01%
CAS: 7446-09-5	Sulfur Dioxide ⚠ Acute Tox. 3, H331; ⚠ Skin Corr. 1B, H314; Press. Gas, H280	0.001-0.01%
CAS: 7727-37-9 RTECS: QW 9700000	Nitrogen ⚠ Press. Gas, H280; Simple Asphyxiant	99.98-99.998%

* **4 First-Aid Measures**

- **Description of first aid measures:**
- **General information:**
Symptoms may even occur after several hours; therefore observe area effected for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Generally the product does not irritate the skin.
In cases of contact with liquified material, frostbite may occur. Immerse frostbite in cool-warm water and seek medical attention.
Wash with soap and water.
If skin irritation occurs, consult a doctor.
- **After eye contact:**
Not anticipated under normal use.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Not a normal route of entry.
If swallowed and symptoms occur, consult a doctor.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/09/2015

Reviewed on 11/09/2015

Trade name: Precision Calibration Gas Mixture

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed:**
No further relevant information available.

* 5 Fire-Fighting Measures

- **Extinguishing media:**
- **Suitable extinguishing agents:**
Use fire fighting measures that suit the environment.
Use water spray to cool fire-exposed containers.
- **Special hazards arising from the substance or mixture:**
Closed containers may explode when exposed to extreme heat.
If incinerated, product will release the following toxic fumes: Oxides of Nitrogen (NOx) and Sulfur.
- **Advice for firefighters:**
This gas mixture is not flammable; however, container, when involved in fire, may rupture or burst in the heat of the fire. Firefighters should be aware of the presence of Hydrogen Sulfide in the gas mixture, which can cause significant health effects.
- **Protective equipment:**
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

* 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**
Treat any fumes as toxic.
Keep away from ignition sources
Ensure adequate ventilation.
Keep people at a distance and stay upwind.
In a confined area, NIOSH approved respiratory protection may be required.
- **Environmental precautions:** Inform authorities in case of gas release.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Dispose of the collected material according to regulations.
- **Reference to other sections:**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* 7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Be aware of any signs of dizziness or fatigue; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms due to the potential for oxygen deficiency (simple asphyxiation). Do not attempt to adjust, repair or in any other way modify the cylinders containing this gas mixture. If there is a malfunction or another type of operational problem, contact nearest distributor immediately.
- **Information about protection against explosions and fires:**
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
Do not cut, grind or weld on container that contains or contained product.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/09/2015

Reviewed on 11/09/2015

Trade name: Precision Calibration Gas Mixture

Do not spray on a naked flame or any incandescent material.

- **Conditions for safe storage, including any incompatibilities:**

Store away from strong oxidizing agents, strong bases, strong reducing agents, and Zinc.

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Cylinders should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature. Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a "first-on, first-out" inventory system to prevent full containers from being stored for long periods of time.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s):** No further relevant information available.

* 8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

- **Components with occupational exposure limits:**

7727-37-9 Nitrogen

TLV | withdrawn TLV, see App. F; simple asphyxiant

7783-06-4 Hydrogen Sulfide

PEL | Ceiling limit value: 20; 50* ppm

*10-min peak; once per 8-hr shift

REL | Ceiling limit value: 15* mg/m³, 10* ppm

*10-min

TLV | Short-term value: 7 mg/m³, 5 ppm

Long-term value: 1.4 mg/m³, 1 ppm

7446-09-5 Sulfur Dioxide

PEL | Long-term value: 13 mg/m³, 5 ppm

REL | Short-term value: 13 mg/m³, 5 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV | Short-term value: 0.65 mg/m³, 0.25 ppm

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

- **Exposure controls:**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/09/2015

Reviewed on 11/09/2015

Trade name: Precision Calibration Gas Mixture**· Breathing equipment:**

Suitable respiratory protective device recommended.

- **Protection of hands:** Not required.
- **Material of gloves:** Not required.
- **Penetration time of glove material:** Not applicable.
- **Eye protection:** Not necessary under normal conditions.
- **Body protection:** Not required.

* **9 Physical and Chemical Properties****· Information on basic physical and chemical properties****· General Information****· Appearance:****Form:** Compressed gas**Color:** Clear, colorless**· Odor:** Rotten**· Odor threshold:** Not determined.**· pH-value:** Not determined.**· Change in condition****Melting point/Melting range:** Not determined.**Boiling point/Boiling range:** Not determined.**· Flash point:** None**· Flammability (solid, gaseous):** Not determined.**· Ignition temperature:** Not determined**· Decomposition temperature:** Not determined.**· Auto igniting:** Product is not self-igniting.**· Danger of explosion:** Not determined.**· Explosion limits:****Lower:** Not determined.**Upper:** Not determined.**· Vapor pressure:** Not determined.**· Density:****Relative density:** Not determined.**Vapor density:** Not determined.**Evaporation rate:** Not applicable.**· Solubility in / Miscibility with:****Water:** Not miscible or difficult to mix.**· Partition coefficient (n-octanol/water):** Not determined.**· Viscosity:****Dynamic:** Not determined.**Kinematic:** Not determined.

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/09/2015

Reviewed on 11/09/2015

Trade name: Precision Calibration Gas Mixture

· **Other information:** No further relevant information available.

*** 10 Stability and Reactivity**

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** Strong oxidizing agents, strong bases, strong reducing agents, and Zinc.
- **Hazardous decomposition products:** Nitrogen Oxides (NOx), and Sulfur Oxides.

*** 11 Toxicological Information**

- **Information on toxicological effects:**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

7783-06-4 Hydrogen Sulfide

Inhalative	LC50/4 h	634 mg/l (mouse) 444 mg/l (rat)
	LC50/96 hours	0.016 mg/l (Pimephales)

7446-09-5 Sulfur Dioxide

Inhalative	LC50/4 h	5040 mg/l (rat)
------------	----------	-----------------

- **Primary irritant effect:**
- **On the skin:** No irritating effect.
- **On the eye:** No irritating effect.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
- **Carcinogenic categories:**
- **IARC (International Agency for Research on Cancer):**
Group 1 - Carcinogenic to humans
Group 2A - Probably carcinogenic to humans
Group 2B - Possibly carcinogenic to humans
Group 3 - Not classifiable as to its carcinogenicity to humans
Group 4 - Probably not carcinogenic to humans

7446-09-5	Sulfur Dioxide	3
-----------	----------------	---

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

*** 12 Ecological Information**

- **Toxicity:** The hazards for the aquatic environment are unknown.
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/09/2015

Reviewed on 11/09/2015

Trade name: Precision Calibration Gas Mixture

- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Generally not hazardous for water.
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

*** 13 Disposal Considerations**

- **Waste treatment methods:**
- **Recommendation:**
Observe all federal, state and local environmental regulations when disposing of this material.
Release all residual gas pressure in a well ventilated area. Verify the cylinder is completely empty (0 PSIG).
Remove or cover any hazard labels. Return empty cylinder for recycling.
NOTE: Check with the local waste authority before placing any gas cylinder into waste container for pickup.
GASCO encourages the consumer to return all cylinders.
- **Waste disposal key:**
The U.S. EPA has not published waste disposal numbers for this product's components.
- **Uncleaned packagings:**
- **Recommendation:** Return cylinder and unused product to supplier.

*** 14 Transport Information**

- **UN-Number:**
- **DOT, ADR, IMDG, IATA** UN1956
- **UN proper shipping name:**
- **DOT, IATA** Compressed gas, n.o.s.
- **ADR** UN1956 Compressed gas, n.o.s.
- **IMDG** COMPRESSED GAS, N.O.S.
- **Transport hazard class(es):**
- **DOT**



- **Class:** 2.2
- **Label:** 2.2

- **ADR**



- **Class:** 2.2 1A
- **Label:** 2.2

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/09/2015

Reviewed on 11/09/2015

Trade name: Precision Calibration Gas Mixture· **IMDG, IATA**

- **Class:** 2.2
- **Label:** 2.2
- **Packing group:**
- **DOT, ADR, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Danger code (Kemler):** 20
- **EMS Number:** F-C,S-V
- **Stowage Category** A
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **Transport/Additional information:**
- **DOT**
- **Quantity limitations:** On passenger aircraft/rail: 75 kg
On cargo aircraft only: 150 kg

- **ADR**
- **Excepted quantities (EQ):** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

- **IMDG**
- **Limited quantities (LQ):** 120 ml
- **Excepted quantities (EQ):** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- **UN "Model Regulation":** UN 1956 COMPRESSED GAS, N.O.S., 2.2

* **15 Regulatory Information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

· **Section 355 (extremely hazardous substances):**

7783-06-4	Hydrogen Sulfide
7446-09-5	Sulfur Dioxide

· **Section 313 (Specific toxic chemical listings):**

7783-06-4	Hydrogen Sulfide
-----------	------------------

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **California Proposition 65:**· **Chemicals known to cause cancer:**

None of the ingredients are listed.

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/09/2015

Reviewed on 11/09/2015

Trade name: Precision Calibration Gas Mixture

· Chemicals known to cause reproductive toxicity for females:
None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:
None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:
None of the ingredients are listed.


· Carcinogenic categories:
· EPA (Environmental Protection Agency):
7783-06-4 Hydrogen Sulfide I

· TLV (Threshold Limit Value established by ACGIH):
7446-09-5 Sulfur Dioxide A4

· NIOSH-Ca (National Institute for Occupational Safety and Health):
None of the ingredients are listed.

· **GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**

GHS04 GHS07

· **Signal word:** Warning· **Hazard statements:**

Contains gas under pressure; may explode if heated.

Harmful if inhaled.

May displace oxygen and cause rapid suffocation.

· **Precautionary statements:**

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

Protect from sunlight. Store in a well-ventilated place.

· National regulations:
The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· State Right to Know:
CAS: 7727-37-9 Nitrogen 99.98-99.998%
RTECS: QW 9700000 ⚠ Press. Gas, H280; Simple Asphyxiant
CAS: 7783-06-4 Hydrogen Sulfide 0.001-0.01%
⚠ Flam. Gas 1, H220; ⚠ Acute Tox. 2, H330; ⚠ Aquatic Acute 1, H400; Press. Gas, H280
CAS: 7446-09-5 Sulfur Dioxide 0.001-0.01%
⚠ Acute Tox. 3, H331; ⚠ Skin Corr. 1B, H314; Press. Gas, H280
All ingredients are listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/09/2015

Reviewed on 11/09/2015

Trade name: Precision Calibration Gas Mixture*** 16 Other Information****· Relevant phrases:**

Gasco Affiliates, LLC, makes not express or implied warranties, guarantees or representations regarding the product of the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Gasco Affiliates, LLC shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use of reliance upon the information herein.

· Date of preparation / last revision: 11/09/2015 / -**· Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Flam. Gas 1: Flammable gases, Hazard Category 1
 Press. Gas: Gases under pressure: Compressed gas
 Acute Tox. 2: Acute toxicity, Hazard Category 2
 Acute Tox. 3: Acute toxicity, Hazard Category 3
 Acute Tox. 4: Acute toxicity, Hazard Category 4
 Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B
 Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

· * Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106